

Specification for Approval

Customer:	
Customer P/N:	
EEC P/N:	DG36001N0
Spec No.:	
Version No.:	V0.1
Description:	100/1000 BASE-T
	Laser Marking

Customer Approval		EEC Approval	
Inspected By:		Issued By:	Xingyu,He
Checked By:		Checked By:	Duffy
Approved By:		Approved By:	Jerry
Approved Date:		Issued Date:	2024/7/15

Please Return One Copy to Us After Approved,TKS! (承认后请回寄一份,谢谢)

- Remark:
- 1. Before use, please confirm whether this product is suitable for your design, Scientific only ensure products meet this specification.
 - 2. This specification data change must be confirmed by both parties,any individual modification is invalid.
 - 3. If customer placed orders without signing back this specification, it is regarded as recognition



绵阳敦源电子科技有限公司
Mianyang Dunyuan Electronics Technology Co.,Ltd
地址：四川省绵阳市高新区综合保税区
ADD: Comprehensive Bonded Zone, High-Tech Industrial Development Zone Mianyang, SiChuan


Specification for Approval

Revision History


[illegible]

DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
100/1000 BASE-T	DG36001N0		PAGE: 1/4

A. MECHANICAL(unit:mm)



B. Schematics



DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
100/1000 BASE-T	DG36001N0		PAGE: 2/4




Specification for Approval

C. ELECTRICAL SPECIFICATIONS @25°C

Unless Otherwise Specified, Testing is Performed at 25°C ± 5°C


1. OCL: 350 uH Min @ 100 KHz, 0.1V with 8mA DC BIAS
2. Leakage Inductance: 0.5uH Max @ 100KHz, 0.1V
3. DCR: 1400mΩ Max
4. Turns Ratio: 1CT:1CT±5%
5. Insertion Loss: -1.1 dB Max @ 1-100 MHz
6. Return Loss: -18 dB Min @ 1-30 MHz
 - 14.4 dB Min @ 40 MHz
 - 13.1 dB Min @ 50 MHz
 - 12 dB Min @ 60-80 MHz
 - 10 dB Min @ 100 MHz
7. Cross Talk: -30 dB Min @ 1-100 MHz
8. Common Mode Rejection: -30 dB Min @ 1-100 MHz
9. Isolation Hipot: 1500VAC 1mA 60S
10. Operating temperature 0°C to +70°C
11. Storage temperature -40°C to +85°C

D. RECOMMEND WAVE SOLDERING CURVE




DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
100/1000 BASE-T	DG36001N0		PAGE: 3/4


E. Packaging specification



Tube: 530*10.6*18.2mm



Inner Carton: L555*W165*H100mm



Export Carton: L570*W370*H240mm

Package Quantity:

One Tube=15Pcs

One Inner Carton=15*70=1050Pcs

One Export Carton=1050*4=4200Pcs

DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
100/1000 BASE-T	DG36001N0		PAGE: 4/4