

1		2		3		4		5		6		7		8	
芯数		2芯		3芯		4芯		5芯		6芯		7芯		8芯	
接触对排列分布 从针的方向看															
额定电流/电压		10A-250V		10A-250V		10A-250V		10A-150V		7A-150V		7A-150V		5A-150V	
工作电压 (AC.V) 分钟		250		250		250		200		200		200		200	
耐电压 (AC.V) 1分钟		1500		1500		1500		1000		1000		1000		1000	
绝缘阻抗 (MΩ) DV500V		1500		1500		1500		1000		1000		1000		1000	
接触阻抗 (MΩ) DC1A		3		3		3		3		3		3		3	
焊杯口径 φ (mm)		2		2		2		1.2		0.8		0.8		0.8	
接触孔孔径 φ (mm)		2.95		2.95		2.95		2.95		2		2		1.5	

1). 未注公差±0.5

2) 接触方式：螺母连接

3) 接插次数：500次

4) 温度范围：-20℃~+85℃

6) 接触体材料：铜（镀金/银）

序号	图号	名称	数量	材料	处理
1		插座外壳	1	锌合金	镀镍
2		铜针		铜	镀金/镀银
3		垫圈	1	钢	
4		六角螺母	1	锌合金	镀镍
5		绝缘件	1	电木	

GX20-H-**-A-A

Material Attribute: Standard

Mold Number: A136

Pin Layout:02-15PIN

Port: F-Female / H-Male

Series:GX20

SAMZO COMPONENTS

Electronic switch and connector manufacturer

REV	ECN NO	DESRIPTION	DESIGN	APPROVAL	DATE	DESIGN	WANGGUIFA	2013.02.12
A1	NEW	Replace frame			2013.02.12	CHECKED	ZHENGUILAN	2013.02.12
						APPROVED	LILIANJIANG	2013.02.14

GENERAL TOLERANCE

≥0~2< ±0.15

≥2~5< ±0.25

≥5 ±0.35

FIRST VIEW

SCALE 1:1 UNIT mm

SVHC/ROHS

The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts.

WWW.KKK-JP.COM

TITLE:: GX20公端

PART NO: GX20-H-XX-A-A

DWG NO: GX20-P136

MODEL NO: GX20H1130

NAME: Aviation connector