

Preliminary DATA SHEET

GSM2424C: 2300 to 2400MHz High Linearity 24dBm Power Amplifier

Product overview

GSM2424C is a two-stage HBT small cell power amplifier for indoor cellular base stations. It works at 2300~2400 MHz (band 40). This PA can deliver 24dBm output power with ACPR below -48dBc and power gain higher than 30dB




Figure 1. 14 Pad 7 x 7 mm Laminate Package

Key Features

- 2300MHz – 2400MHz
- 28dB Gain
- 16% PAE at 24dBm output power
- Below -50dBc ACPR at 24dBm output power
- Input/output internally matched to 50Ohm
- Integrated temperature compensation circuits (MSL3, 260°C per JEDEC J-STD-020)
- ESD Level: HBM 1000V; CDM 1000V
- ROHS compatible




Figure 2. GSM2424C Function Block Diagram

Applications

- FDD and TDD 2G/3G/4G LTE/5G NR systems
- 3GPP LTE band 40, and 5G NR n40 for base-station application
- Driver amplifier for micro-base and macro-base stations
- Active antenna array and massive MIMO
- Customer Premises Equipment (CPE)
- Automotive Compensator

Table 1. Pin-to-Pin Compatible PA Family

Part Num	Frequency (MHz)	3GPP Band
GSM1824C	1805-1880	Band 2,3, 34,39, n2, n3
GSM2124C	2110-2170	Band 1, n1
GSM2424C	2300-2400	Band 40, n40

Ordering Information

Part No.	Description
GSM2424C	2300-2400MHz 24dBm linear PA, 7' Reel with 1500pcs