



Connectors > Automotive Connectors > Automotive Housings



Connector System: **Wire-to-Wire**  
Number of Positions: **4**  
Connector & Housing Type: **Housing for Male Terminals**  
Centerline (Pitch): **5 mm [ .196 in ]**  
Sealable: **No**

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing

Configuration Features

Number of Positions	4
Number of Rows	2

Electrical Characteristics

Nominal Voltage Architecture	12 V
------------------------------	------

Body Features

Primary Product Color	Black
-----------------------	-------



Connector & Keying Code	D
Contact Features	
Contact Size	1.2mm
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	5 mm[.196 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Other	
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 963143-1  
MQS BLINDSTOPFEN

TE Part # CAT-M4595-T273  
MCON Receptacle and Tab

TE Part # 2356607-4  
4POS,MCON 1.2,REC HSG ASSY,SLD, COD D

Also in the Series | Superseal Pro

Automotive Housings(87)

Connector Backshells(14)

Connector Caps & Covers(1)

Other Automotive Connector Accessories(1)

Customers Also Bought

TE Part #788189-2  
CPC 17-3 RCPT ASY,REV SEX

TE Part #2-330648-1  
PIDG 22-16 22-18 MIL R 4; TAPE

TE Part #2177090-3  
STEEL,OUTER FERRULE,8MM HV, 25SQMM

TE Part #1-1633961-2  
CRIMPER, INSULATION F PREMIUM





TE Part #1587940-3  
CABLE SEAL RETAINER, SIZE C



TE Part #2103013-3  
CABLE SEAL RETAINER, SIZE 2, OR, HVA280



TE Part #2208669-3  
8MM HV, CONTACT, ASSY



TE Part #4-1633932-0  
ANVIL, COMBINATION



TE Part #464291-5  
ANVIL, SAND-BLASTED 12-10



TE Part #YHV280-2PM-P-4MM-B  
HVA280-2phm,pass,4sqmm,Key B

Documents

Product Drawings

4POS,MCON 1.2,TAB HSG ASSY,SLD,COD D

English

4POS,MCON 1.2,TAB HSG ASSY,SLD,COD D

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2356631-4\_C.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2356631-4\_C.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2356631-4\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Superseal Pro Connector series-Applications

English

Product Specification

English

Product Specification

English

2356631-4

Housing for Male Terminals, Wire-to-Wire, 4 Position, .196 in [5 mm] Centerline,  
Black, Wire & Cable, Power & Signal, Superseal Pro

