

Engineer Drawing

SPECIFICATIONS

1. Current rating: 5A AC, DC
2. Voltage rating: 250V AC,DC
3. Temperature range: -40°C ~ +105°C
4. Insulation resistance: 1000MΩ Min.
5. Withstanding voltage: 1500V AC/ minute.
6. Contact resistance: 10mΩ Max.

Material: PA66 UL94 V-0 or V-2

Circuits: 2~12

IPCW 300 H X X X X XX X

Series Type

Pitch:3.00mm

Connector Type

Rows Code

Other Code

Pin Code

Material Code

Colour Code

Internal Code

Circuits	Dimensions	
	A	B
2P	3.0	7.00
3P	6.0	10.00
4P	9.0	13.00
5P	12.0	16.00
6P	15.0	19.00
7P	18.0	22.00
8P	21.0	25.00
9P	24.0	28.00
10P	27.0	31.00
11P	30.0	34.00
12P	33.0	37.00

TOLERANCES:

X.=±0.30

X.X=±0.20

X.XX=±0.10

GENERAL ANGLE

X°=±2°

NCP

PART NO:
IPCW300H xx 0C0

DRAWING NO
IPCW300H0C0

 SHEET 1 OF 1

www.i-ncp.com

NAME:
3.0mmPH Male Housing
Single Row

UNITS:mm SCALE:1:1 REV.01

