


SURFACE MOUNT GENERAL RECTIFIER

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Features

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ Idea for printed circuit board
- ◆ Glass passivated Junction chip
- ◆ Low reverse leakage
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed
250 C/10 seconds at terminals

Mechanical Data

- ◆ **Case :** JEDEC DO-214AC/SMA Molded plastic body
- ◆ **Terminals :** Solder plated, solderable per MIL-STD-750, Method 2026
- ◆ **Polarity :** Polarity symbol marking on body
- ◆ **Mounting Position :** Any
- ◆ **Weight :** 0.0023 ounce, 0.07 grams

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	SYMBOLS	1N4001	1N4002	1N4003	1N4004	1N4005	1N4006	1N4007	UNITS
		M1	M2	M3	M4	M5	M6	M7	
Marking Code									
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current at TL=110°C	I _(AV)								A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}								A
Maximum instantaneous forward voltage at 1.0A	V _F								V
Maximum DC reverse current TA=25°C at rated DC blocking voltage TA=125°C	I _R				5				uA
Typical junction capacitance (NOTE 1)	C _J				15.0				pF
Typical thermal resistance (NOTE 2)	R _{θJA}				75.0				°C/W
Operating junction and storage temperature range	T _J , T _{STG}				-55 to +150				°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. P.C.B. mounted with 0.2x0.2" (5.0x5.0mm) copper pad areas

Fig.1 Forward Current Derating Curve




Fig.2 Typical Instantaneous Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Repetitive Peak Forward Surge Current



PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SMA



The recommended mounting pad size

