

承 认 书

SPECIFICATION FOR APPROVAL

客 户 Customer:

产品名称 Project:

贴片电感

规格型号 Part No:

CD75-XXXM

贵公司承认印 Approval signatures

料 号/Part No.	签 章/Signatures

日期 Date:

拟制/Drawn	王宗华	
审核/Check	陈淼淼	
批准/Approved	张春华	


1.Features

- ①. High performance (Isat) realize by metal dust core.
- ②. Low profile: Thickness max.2.0~5.0mm.
- ③. Low loss and low resistance.
- ④. Capable of corresponding high frequency 1MHz~5MHz.
- ⑤ Ultra low buzz noise, due to composite construction.
- ⑥. The products contain no lead and also support lead-free soldering.


2.Applications area

Ideally used in NB/Desktop/server/Graphic card, LCD TV/Projector, etc as DC-DC Converter.

3. Externl Dimensions (unit: mm)



4. Product Code



Code 代码	Tolerance 公差
J	±5%
K	±10%
L	±15%
M	±20%
P	±25%
N	±30%

- 电感值Inductance Value
(1R0:1.0uH; 100: 10uH; 101:100uH)

5. Electrical Characteristics

HY75 type

PART No.	NOMINAL INDUCTANCE (μ H)	Test Freq. (kHz/v)	DCR (Ω)MAX	IDC (A)MAX
CD75-1R0M	1.0	100/0.25	13.00m	5.20
CD75-2R7M	2.7	100/0.25	16.90m	4.60
CD75-3R3M	3.3	100/0.25	19.50m	4.00
CD75-3R9M	3.9	100/0.25	23.40m	4.00
CD75-4R7M	4.7	100/0.25	26.00m	3.80
CD75-5R6M	5.6	100/0.25	27.30m	3.10
CD75-6R8M	6.8	100/0.25	32.50m	2.80
CD75-8R2M	8.2	100/0.25	39.00m	2.52
CD75-100M	10	100/0.25	41.60m	2.31
CD75-120M	12	100/0.25	49.40m	2.00
CD75-150M	15	100/0.25	71.50m	1.81
CD75-180M	18	100/0.25	84.50m	1.59
CD75-220M	22	100/0.25	91.00m	1.50
CD75-270M	27	100/0.25	106.60m	1.28
CD75-330M	33	100/0.25	119.60m	1.20
CD75-390M	39	100/0.25	149.50m	1.08
CD75-470M	47	100/0.25	175.50m	1.05
CD75-560M	56	100/0.25	208.00m	930m
CD75-680M	68	100/0.25	234.00m	830m
CD75-820M	82	100/0.25	273.00m	780m
CD75-101M	100	100/0.25	325.00m	730m
CD75-121M	120	100/0.25	390.00m	650m
CD75-151M	150	100/0.25	520.00m	580m
CD75-181M	180	100/0.25	598.00m	510m
CD75-221M	220	100/0.25	793.00m	480m
CD75-271M	270	100/0.25	884.00m	400m
CD75-331M	330	100/0.25	1.13	390m
CD75-391M	390	100/0.25	1.30	350m
CD75-471M	470	100/0.25	1.68	330m
CD75-561M	560	100/0.25	1.90	300m
CD75-681M	680	100/0.25	2.47	270m
CD75-821M	820	100/0.25	2.86	250m


• Notes

1. All test data is referenced to 25 °C ambient

- Operating temperature range - 55 °C to + 125 °C
- Irms (A):DC current (A) that will cause an approximate ΔT of 40 °C(reference ambient temperature is 25 °C)
- Isat(A):DC current (A) that will cause L0 to drop approximately 30 %
- The part temperature (ambient + temp rise) should not exceed 125 °C under worst case operating conditions.
Circuit design, component placement, PWB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
- Absolute maximum voltage 30VDC

6.Minimum Packaging and storage

• 包装Packing




规格 尺寸	13"	7"
A	$\Phi 330 \pm 2.0$	$\Phi 178 \pm 2.0$
B	$\Phi 90 \pm 2.0$	
C	2.3	
D	21.5	1000/盘

• Tape Carrier Packaging:

Type	Standard Quantity (pcs/reel)	Type	Standard Quantity (pcs/reel)
CD43	2000	CD75	1000
CD53	2000	CD77	600
CD54	1500	CD105	1000
CD73	1000	CD106	800

• Recommended reflow soldering curve



• Application Notice

Storage Conditions To maintain the solderability of terminal electrodes:

- Temperature and humidity conditions: Less than 30°C and 70% RH.
- Recommended products should be used within 6 months from the time of delivery.
- The packaging material should be kept where no chlorine or sulfur exists in the air.

Transportation

- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- The use of tweezers or vacuum pick up is strongly recommended for individual components. Bulk handling should ensure that abrasion and mechanical shock are minimized.