

## SHUR-PLUG 180

TE Internal #: 60799-5

Shur-Plug, 4.57 mm [.18 in] Pin Diameter, 18 – 14 AWG, .8 – 2 mm<sup>2</sup>

Wire, 1624 – 4106 CMA, Open Barrel, Tin Plating, SHUR-PLUG 180

View on TE.com >



Terminals & Splices > Crimp Wire Pins, Tabs & Ferrules











Crimp Wire Terminal Type: Shur-Plug

Mating Pin Diameter: 4.57 mm [.18 in]

Compatible Insulation Diameter Range: 3.17 mm, 2.29 – 3.18 mm [ .125 in, .09 – .125 in ]

Wire Size: .8 – 2 mm<sup>2</sup>

## **Features**

## **Packaging Features**

Packaging Quantity	12000
Packaging Method	Reel

## **Product Type Features**

Compatible With Discrete Wire Type	Solid, Stranded	

## **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

## **Contact Features**

Crimp Wire Terminal Type	Shur-Plug
Mating Pin Diameter	4.57 mm[.18 in]
Barrel Type	Open
Terminal Plating Material	Tin
Terminal Orientation	Straight

#### Mechanical Attachment

Wire Insulation Support	With	
-------------------------	------	--

## **Dimensions**



Compatible Insulation Diameter Range	3.17 mm, 2.29 – 3.18 mm[.125 in][.09 – .125 in]
Wire Size	1624 – 4106 CMA
Barrel Inside Diameter	2.66 mm, 1.65 mm[.105 in][.065 in]
Terminal Material Thickness	.39 mm[.016 in]
Overall Product Length	22.73 mm[.895 in]

## **Usage Conditions**

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]

#### Other

EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Compatible Parts





## Also in the Series | SHUR-PLUG 180







Crimp Wire Pins, Tabs & Ferrules(37)



Special Purpose Terminals(1)

## Customers Also Bought



TE Part #TAA755A5501-040 M12A5-MS-FS-PUR-4.0M






















## **Documents**

## **Product Drawings**

SHUR PLUG 180 RECEPTACLE 18-14 AWG TPBR

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_60799-5\_AL.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_60799-5\_AL.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_60799-5\_AL.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English