





深圳市首韩科技有限公司

SHENZHEN SHOUHAN TECHNOLOGY CO., LTD

Tel: 0755-27597601 Fax: 0755-27597491

## 承 认 书

### SPECIFICATION FOR APPROVAL

产 品 编 码

Material code:

产品名称 Project:

微动开关

规格型号 Part No:

3JWD-WBHD 125

贵公司承认印 Approval signatures

| 料 号/Part No. | 签 章/Signatures |
|--------------|----------------|
|              |                |

日期 Date:

|             |     |                                                                                      |
|-------------|-----|--------------------------------------------------------------------------------------|
| 拟制/Drawn    | 李春风 |  |
| 审核/Check    | 钟华华 |                                                                                      |
| 批准/Approved | 罗孝金 |                                                                                      |



## 规格书 SPECIFICATION

### 1. 一般特性 General Characteristics

- 1.1 额定值(Rating Value): AC 125V 0.05A
- 1.2 工作温度(Work Temperature Range): 25℃ ~ 85℃
- 1.3 贮存温度(Store Temperature Range): -25℃ ~ 85℃
- 1.4 正常测试条件(未有特殊说明量测在以下条件进行):

General test condition (Tests and measurements shall be made under the following standard conditions unless otherwise specified):

正常温度: 5℃~35℃      相对湿度: 45%~98% RH      气压: 8,600~10,600 帕  
Temperature: 5℃~35℃      Relative humidity: 45%~98%      Air pressure: 8,600~10,600 pa

### 2. 产品外观及尺寸要求 Appearance & Dimension Requirement

- 2.1 产品外形结构紧凑, 无配合不良.  
The structure of product is compact, and assembly of parts has no badness.
- 2.2 产品塑胶部件无严重缩水、披锋、欠注、斑点、破损或变形现象.  
The plastic parts of product have no serious defects such as very serious shrink, scarcity, fleck, disrepair, transmutation, etc.
- 2.3 产品引脚和外壳无严重氧化、脏污、变形、毛刺或电镀不良.  
Lead feet and shell have no serious defects such as oxidation, smudge, disrepair, burr, defects on plating.
- 2.4 开关操作顺畅, 节奏感强, 无明显卡塞现象.  
Operating switch is unhindered, rhythmmed, and there is not palpable clag.
- 2.5 产品结构及尺寸参见产品规格图纸.  
Construction and dimensions: Refer to individual product drawing.

### 3. 电气特性 Electronic Characteristics

| No. | 项 目<br>Item                          | 测试方法<br>Test Method                                                                                                                                                                     | 测试设备<br>Equipment                     | 特性要求<br>Requirements                                                |
|-----|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------|
| 3.1 | 接触电阻<br>Contact Resistance           | 在低电流(≤100mA)条件下测试.<br>Measured at low current (100mA or less).                                                                                                                          | 低电阻测试仪<br>Low Resistance Meter        | 100mΩ MAX                                                           |
| 3.2 | 绝缘阻抗<br>Insulation Resistance        | 测试相邻引脚之间, 引脚与外壳之间的绝缘阻抗.<br>Measurement shall be made between adjacent terminals, between terminal and shell.                                                                            | 绝缘测试机<br>Insulation Resistance Tester | 100MΩ MIN                                                           |
| 3.3 | 耐压测试<br>Dielectric Withstand Voltage | 输入一定电压(50~60Hz, 电压值 AC 250V) 1 分钟, 漏电流为 2mA, 测试邻近端子间.<br>Apply certain voltage (50~60Hz, AC 250V) for 1 minute between adjacent contacts of the connector with 2mA leakage sensitivity. | 耐压测试机<br>Puncture Tester              | 没有绝缘破坏.<br>电弧等异常.<br>No arcing, break down and damaging insulation. |

## 4. 机械特性 Mechanical Characteristics

| No. | 项 目<br>Item              | 测试方法<br>Test Method                                                                                                                                                                             | 测试设备<br>Equipment  | 特性要求<br>Requirements |
|-----|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------------------|
| 4.1 | 操 作 力<br>Operation Force | 逐渐施力操作开关按键，测量开 关到达全部工作行程时所需的最大操作力度。<br>Operate the keystroke of the switch and then increase press strength gradually, Measured maximum operation force while the travel of the switch is full. | 测力计<br>Force Gauge | 110±15gf             |

## 5. 可靠性测试 Reliability trial

| No. | 项 目<br>Item                          | 测试方法<br>Test Method                                                                                                                                                   | 测试设备<br>Equipment    | 特性要求<br>Requirements                                                                                                                                                                                                                                                                   |
|-----|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5.1 | 可焊性试验<br>Solder ability Test         | 端子顶部被浸入焊锡炉中，温度为 260±5℃，时间 5±1 秒。<br>The top of the terminals shall be dipped in the solder bath at 260±5℃ for 5±1 seconds.                                            | 控温锡炉<br>Solder Stove | 引脚至少 95%上锡。<br>Ninety-five percent of terminals shall be dipped.                                                                                                                                                                                                                       |
| 5.2 | 寿命试验<br>Operation Life               | 开关在寿命试验设备上以约 90 次 / 分的速度连续被操作，具体次数见规格图示。<br>Switch shall be operated continuously at about 90 cycles /min without load.                                               | 寿命试验机<br>Life Tester | 寿命:50000 次<br>实验后:<br>绝缘电阻: 100MΩ Min<br>操作力: 变化在±50%内开关外观及结构无损坏。<br>Life test:50000 cycles<br>After test, Insulation resistance:10MΩ Min<br>Operating force: Change should be within ±50% of specified value.<br>No abnormalities shall be recognized in appearance and construction. |
| 5.3 | 耐焊接热<br>Resistance to Soldering heat | 端子焊接部分浸入焊炉，焊炉温度 250± 5℃，焊接时间 5±1 秒。(焊接时不可于 端子施加外力)。<br>Terminals shall be dipped in the solder bath at 250±5℃ for 5±1 seconds without additional force for terminals. | 控温锡炉<br>Solder Stove | 本体无变形，能满足于机械、电气性能。<br>Appearance should be not damaged, electrical and mechanical characteristics shall be satisfied.                                                                                                                                                                  |

## 5. 可靠性测试 Reliability trial

| No. | 项 目<br>Item                          | 测试方法<br>Test Method                                                                                                                                                                                                                                                                                                                                                          | 测试设备<br>Equipment                              | 特 性 要 求<br>Requirements                                                                       |
|-----|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|-----------------------------------------------------------------------------------------------|
| 5.4 | 耐高温测试<br>Resistance to Heat Test     | 放置在温度 $80\pm 2^{\circ}\text{C}$ 环境中 96 小时后，再置于正常条件下 1 小时后测定。<br>The switch shall be stored at a temperature of $80\pm 2^{\circ}\text{C}$ for 96 hours, Measurements shall be made after it be subjected to the standard conditions for 1 hour.                                                                                                                               | 高低温试验机<br>High & Low Temperature Tester        | 外观，机械及电气性能均符合要求。<br>Appearance, electrical and mechanical characteristics shall be satisfied. |
| 5.5 | 耐低温测试<br>Resistance to Cold Test     | 放置在温度 $-20\pm 2^{\circ}\text{C}$ 环境中 96 小时后，再置于正常条件下 1 小时后测定。<br>The switch shall be stored at a temperature of $-20\pm 2^{\circ}\text{C}$ for 96 hours, Measurements shall be made after it be subjected to the standard conditions for 1 hour.                                                                                                                             | 高低温试验机<br>High & Low Temperature Tester        | 外观，机械及电气性能均符合要求。<br>Appearance, electrical and mechanical characteristics shall be satisfied. |
| 5.6 | 耐湿性测试<br>Resistance to Humidity Test | 放置于温度 $40\pm 2^{\circ}\text{C}$ ，相对湿度为 90~96% 环境中 96 小时后，再置于正常条件下 1 小时后测定(注意要擦去水滴)。<br>The switch shall be stored at a temperature of $40\pm 2^{\circ}\text{C}$ , relative humidity 90~96% for 96 hours, Measurements shall be made after it be subjected to the standard conditions for 1 hour (Wipe out water drip).                                                       | 恒温恒湿箱<br>Temperature & Humidity Tester Chamber | 外观，机械及电气性能均符合要求。<br>Appearance, electrical and mechanical characteristics shall be satisfied. |
| 5.7 | 盐雾实验<br>Salt Mist Test               | 试件在下述实验后测量：<br>1. 温度： $35\pm 5^{\circ}\text{C}$<br>2. 盐溶液浓度： $5\pm 1\%$ （质量百分比），<br>3. 试验时间： 24 小时，<br>4. 试验后，将盐沉积物用水冲掉。<br>The switch shall be checked after following test:<br>1. Temperature: $35\pm 5^{\circ}\text{C}$<br>2. Salt solution: $5\pm 1\%$ (Solids by mass)<br>3. Duration: 24 hours,<br>4. After immersing, salt deposit shall be removed by running water. | 盐雾试验机<br>Salt Spray Tester                     | 在金属件上没有严重腐蚀斑点。<br>No remarkable corrosion shall be recognized in metal parts.                 |