

1		2		3		4		5		6		7		8																																	
芯数		2芯		3芯		4芯		5芯		6芯		7芯		8芯																																	
E	接触对排列分布 从针的方向看																																														
	额定电流/电压	7A-125V		7A-125V		7A-125V		7A-125V		5A-125V		5A-125V		5A-125V																																	
	工作电压 (AC.V) 分钟	200		200		200		200		200		200		200																																	
	耐电压 (AC.V) 1分钟	1500		1500		1500		1500		1500		1500		1500																																	
	绝缘阻抗 (MΩ) DV500V	1500		1500		1500		1500		1500		1500		1500																																	
	接触阻抗 (MΩ) DC1A	5		5		5		5		5		5		5																																	
焊杯口径 φ (mm)		1.6		1.6		1.6		1.2		0.9		0.9		0.9																																	
接触对孔径 φ (mm)		2.45		2.45		2.45		2		1.15		1.15		1.15																																	
1). 未注公差±0.5 2) 接触方式; 螺母连接 3) 接插次数: 500次 4) 温度范围; -20℃~+85℃ 6) 接触体材料; 铜(镀金/银) 7) 电缆通过直径 φ 7.5mm~φ 8.5mm 序号 图号 名称 数量 材料 处理 1 压线块 1 锌合金 镀镍 2 压线块螺丝 2 钢 3 母头外壳 1 锌合金 镀镍 4 胶芯固定螺丝 1 钢 5 连接螺母 1 锌合金 镀镍 6 铜针 铜 镀金/镀银 7 绝缘件 1 电木 GX16-F-**-A-A Material Attribute: Standard Mold Number: A085 Pin Layout: 02-10PIN Port: F-Female / H-Male Series: GX16 SAMZO COMPONENTS Electronic switch and connector manufacturer REV ECN NO DESCRIPTION DESIGN APPROVAL DATE DESIGN WANGGUIFA 2013.02.12 A1 NEW Replace frame 2013.02.12 CHECKED ZHENGUILIAN 2013.02.12 APPROVED LILIANJIANG 2013.02.14 FIRST VIEW SCALE 1:1 UNIT mm The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM TITLE:: GX16母端 PART NO: GX16-F-XX-A-A DWG NO: GX16-P085 MODEL NO: GX16F0601 NAME: Aviation connector SVHC/ROHS <tr><td colspan="2">1</td><td colspan="2">2</td><td colspan="2">3</td><td colspan="2">4</td><td colspan="2">5</td><td colspan="2">6</td><td colspan="2">7</td><td colspan="2">8</td></tr> <tr><td colspan="2">A</td><td colspan="2">B</td><td colspan="2">C</td><td colspan="2">D</td><td colspan="2">E</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr>																1		2		3		4		5		6		7		8		A		B		C		D		E							
																1		2		3		4		5		6		7		8																	
																A		B		C		D		E																							

1		2		3		4		5		6		7		8	
芯 数		2 芯		3 芯		4 芯		5 芯		6 芯		7 芯		8 芯	
E	接触对排列分布 从针的方向看														
	额定电流/电压	7A-125V		7A-125V		7A-125V		7A-125V		5A-125V		5A-125V		5A-125V	
	工作电压 (AC.V) 分钟	200		200		200		200		200		200		200	
	耐电压 (AC.V) 1分钟	1500		1500		1500		1500		1500		1500		1500	
	绝缘阻抗 (MΩ) DV500V	1500		1500		1500		1500		1500		1500		1500	
接触阻抗 (MΩ) DC1A		5		5		5		5		5		5		5	
焊杯口径 φ (mm)		1.6		1.6		1.6		1.2		0.9		0.9		0.9	
接触对孔径 φ (mm)		2.45		2.45		2.45		2		1.15		1.15		1.15	

D

1. 未注公差±0.5

2. 接触方式：螺母连接

3. 接插次数：500次

4. 温度范围：-20℃~+85℃

6. 接触体材料；铜（镀金/银）

7. 电缆通过直径 φ 7.5mm~φ 8.5mm

C

序号	图 号	名 称	数量	材 料	处 理
1		铜针		铜	镀银/金
2		六角螺母	1	铜	镀镍
3		垫圈	1	钢	镀镍
4		插座外壳	1	锌合金	镀镍
5		绝缘件	1	电木	

B

GX16-H-**-A-A

Material Attribute: Standard

Mold Number: A068

Pin Layout:02-10PIN

Port: F-Female / H-Male

Series:GX16

A

SAMZO COMPONENTS

Electronic switch and connector manufacturer

REV	ECN NO	DESCRIPTION	DESIGN	APPROVAL	DATE	DESIGN	WANGGUIFA	2013.02.12	≥2~5<	±0.25
A1	NEW	Replace frame			2013.02.12	CHECKED	ZHENGUILAN	2013.02.12	≥0~2<	±0.15
						APPROVED	LILIANJIANG	2013.02.14	≥5	±0.35

FIRST VIEW

SCALE

1:1

UNIT

mm

The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts.

WWW.KKK-JP.COM

SVHC/ROHS

TITLE::

GX16公端

PART NO:

GX16-H-XX-A-A

DWG NO:

GX16-P068

MODEL NO:

GX16H0660

NAME:

Aviation connector

1		2		3		4		5		6		7		8	