




Bridge Rectifiers
Reverse Voltage 600-1000v
Forward current-4A


Features

Glass passivated chip
High surge current capability
Ideal for surface mounted applications
Low power loss, high efficiency
Plastic Case Material has UL Flammability



Mechanical Data

Package: GBU
Terminals: Tin Plated leads, solderable per
Mil-STD-750 Method 2026
Polarity: As marked
Molding compound meets UL 94 V-0 flammability rating,
ROHS-compliant



Maximum Ratings (Ta=25°C Unless otherwise

Type Number	SYMBOL	GBU606	GBU608	GBU610	Umit
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	600	800	1000	V
Maximum Average Forward Rectified Current	IO _(AV)	6.0			A
Peak Forward Surge Current 8.3ms Single half-sine-wave superimposed on rated load(JEDEC Method) on rated	IFSM	90.0			A
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃		180.0			
Current squared time @1ms≤t≤8.3≤ms Tj=25℃, Rating of per diode	I ² t	33.6			A ² S
Maximum Forward Voltage at 6 .0A DC	V _{FM}	1.1			V
Maximum Reverse Current TA = 25℃	IR	5			uA
at Rated DC Blocking Voltage TA = 125℃		100			
Typical Thermal Resistance	R _{QJa}	75.0			℃/W
Operating Junction Temperature Range	T _J	—55to+150			℃
Storage Temperature Range	T _{STG}	—55to+150			℃



FIG. 1 MAXIMUM AVERAGE FORWARD CURRENT DERATING




FIG. 2 TYPICAL FORWARD CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPEITIVE SURGE CURRENT






FIG. 4 TYPICAL REVERSE CHARACTERISTICS (per element)





MARKING INFORMATION



= Logo

GBU**** = Date Code Marking

Print according to customer request

PACKING REQUIRMENTS


- Ps The carton packaging

DEVICE TYPE	Q'TY/REE L (pcs)	BOX/CAR TOON	Q'TY/REE L (pcs)
GBU	500	10	5000



Outline Dimensions

GBU



GBU				
DIM	INC HES		MM	
	MIN	MAX	MIN	MAX
A	0.86	0.87	21.8	22.2
B	0.72	0.74	18.3	18.7
C	0.70	0.72	17.8	18.2
D	0.04	0.05	1.05	1.25
E	0.19	0.21	4.85	5.35
F	0.13	0.14	3.3	3.6
G	0.02	0.02	0.4	0.5



Important Statements and disclaimers.

Do not copy or modify file information without permission.

Xumao Micro reserves the right to modify this document and its products.

Specifications are available without prior notice. Customer shall obtain and confirm the latest product information and specifications prior to final design, purchase or use.

Xumao Micro does not assume any implied warranties, including warranties of fitness for special purposes, non-infringement and merchantability.

The products shown here are not designed and licensed for demanding equipment at a level of reliability or for human life and any life-saving related applications or life-sustaining, such as medical devices, transportation equipment, aerospace machinery, and so on. Customers who use or sell these products for such applications do so at their own risk.

As Xumao Micro uses batch number as tracking benchmark, please provide batch number for tracking in case of exception.