


Coupling:	Threaded coupling
Shell material:	Brass with Nickel Plate
Insert material:	bakelite
Contact material:	copper Silver Plate/Nickel
Termination:	Solder
Mating cycle:	500
Cable diameter:	-20°C +85°C



A diagram of a circle containing five dots. The dots are arranged in a pentagonal pattern. The dots are labeled with numbers: 1 (top right), 2 (middle right), 3 (bottom), 4 (middle left), and 5 (top left). A semi-circle is drawn at the top of the circle, above the dots labeled 5 and 1.

A circular diagram with six dots arranged in a hexagonal pattern. The dots are numbered 1 through 6. Dot 1 is at the top right, dot 2 is at the middle right, dot 3 is at the bottom, dot 4 is at the middle left, dot 5 is at the top left, and dot 6 is in the center.

7P

XD - GX12 - NP - *

No. of Pin 2~7 Pin	Contact Type F=Female M=Male
-----------------------	---------------------------------------

NO. of contacts	芯数	2	3	4	5	6	7
Rated current (A)	额定电流	5A	5A	5A	5A	5A	5A
Operation limit voltage(AC.V.rms)	工作电压(AC.V)分钟	200V	125V	125V	125V	125V	125V
Withstanding voltage(AC.V.rms) 1 minute	耐电压	1500	1500	1500	1500	1500	1500
Insulation resistance(m Ω)	绝缘阻抗	2000	2000	2000	2000	2000	2000
Contact resistance (m Ω)	接触阻抗	5	5	5	5	5	5
Solder cup mouth aperture	焊杯口孔径 ϕ (mm)	ϕ 0.8	ϕ 0.8	ϕ 0.8	ϕ 0.8	ϕ 0.8	ϕ 0.8
Solder inter diameter	接触体孔径 ϕ (mm)	ϕ 1.2	ϕ 1.2	ϕ 1.2	ϕ 1.2	ϕ 1.2	ϕ 1.2

			GENERAL TOLERANCE	制 图 DRAWING	 深圳讯答科技有限公司 ShenzhenXundaTechnology Co.,Ltd			
			DIM TOL	审 核 CHECK				
			X.X ±0.30	批 准 APPROVAL	产 品 名 称 TITLE	GX12 航空插头 公头	版 本 REV.	A
1	初版发行		X.XX ±0.20	比 例 SCALE	产 品 料 号 PART NO.	XD-GX12-NP-M	单 位 UNITS	mm
			X.XXX ±0.10					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°	投 影 Projection	 材 料 MATERIAL		页 次 SHEET	1/1