

Specification for Approval

Customer:	
Customer P/N:	
EEC P/N:	ST06709A0
Spec No.:	
Version No.:	V0.1
Description:	Transformer
	Meet AEC-Q200 Standard
	BMS Application



Customer Approval		EEC Approval	
Inspected By:		Issued By:	Bob
Checked By:		Checked By:	
Approved By:		Approved By:	
Approved Date:		Issued Date:	2024/7/10

Please Return One Copy to Us After Approved,TKS! (承认后请回寄一份,谢谢)



- Remark:
- 1. Before use, please confirm whether this product is suitable for your design, Scientific only ensure products meet this specification.
 - 2. This specification data change must be confirmed by both parties,any individual modification is invalid.
 - 3. If customer placed orders without signing back this specification, it is regarded as recognition.



绵阳敦源电子科技有限公司
Mianyang Dunyuan Electronics Technology Co.,Ltd
地址： 四川省绵阳市高新区综合保税区
ADD: Comprehensive Bonded Zone, High-Tech Industrial Development Zone Mianyang, SiChuan

A. MECHANICAL(unit:mm)

Suggested PAD Layout


**B. Schematics**

DESCRIPTION	EEC P/N:	SPEC NO	Version No.: V0.1
Transformer	ST06709A0		PAGE: 2/4

C. ELECTRICAL SPECIFICATIONS @25°C

Unless Otherwise Specified, Testing is Performed at 25°C ± 5°C

1. OCL: 150 uH Min @ 100 KHz, 0.1V
2. Leakage Inductance: 0.5uH Max @ 100KHz, 0.1V
3. DCR: (1 to 3) 700mΩ Max
(6 to 4) 1000mΩ Max
4. Turns Ratio: 1CT:1CT±5%
5. Insertion Loss: -0.5 dB Max @ 4 MHz
6. Return Loss: -20 dB Min @ 4 MHz
7. Common Mode Rejection: -35 dB Min @ 1-100 MHz
8. Isolation Hipot: 4300VDC 1mA 60s or 2600VAC 1mA 10s
9. Operating temperature -40°C to +125°C
10. Storage Temperature(With Package): +10°C to +40°C
11. Storage Temperature(Without Package, Just For Components): -40°C to +125°C
12. RoHS Compliant
13. Qualification: Meet AEC-Q200

D. RECOMMEND WAVE SOLDERING CURVE

MSL:

Grade: 1 level. Floor life: 0.5 year Condition: ≤30°C/60%RH.




Ramp up rate=3°C/s max Ramp down rate=6°C/s max

TL=217°C tL=60s-150s Tp=250+/-3°C Time within 5°C of actual Peak Temperature (tp): 20~40s


Ts min=150°C Ts max=200°C Ts min to Ts max: 60s-180s, 25°C to peak Temperature: 8minutes max

DESCRIPTION	EEC P/N:	SPEC NO	Version No.: V0.1
Transformer	ST06709A0		PAGE: 3/4


E. Packaging specification




Four Reel



Inner Carton



Two Inner Carton



Export Carton

Package Quantity:

One Reel=600Pcs

One Inner Carton=600*4=2400Pcs

One Export Carton=2400*2=4800Pcs

DESCRIPTION	EEC P/N:	SPEC NO	Version No.: V0.1
Transformer	ST06709A0		PAGE: 4/4