



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	1 of 19

Specification for 5.83"EPD

Model NO.: E0583A52

Product VER: A0

Customer Approval

Customer	
Approval By	
Date Of Approval	

It will be agreed by the receiver, if not sign back the Specification within 15days.

Prepared By	Checked By	Approval By
周涛涛	文伟	王浩



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	2 of 19

Version	Content	Date	Producer
A0	New release	2024/2/22	Leslie



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	3 of 19

CONTENTS

1.General Description	4
2.Features.....	4
3.Typical Application.....	4
4.Mechanical Specifications	4
5.Mechanical Drawing of EPD module	5
6.Input/output Terminals	6
7.Reference Circuit	7
8.Absolute Maximum Rating	9
9.DC Characteristics	9
10.Power Consumption.....	9
11.Optical Characteristics	10
11.1Optical Measurement Conditions	10
11.2Optical Measurement	10
11.3Definition of Contrast ratio	11
11.4Reflection Ratio	11
12.Handling Safety And Environmental Requirements	12
13.Reliability Test	14
14.Block Diagram.....	15
15.Shipment Inspection Specification	15
15.1Zone Definition	15
15.2Line/Spot defect size	15
15.3Point and line standard	16
15.4Barcode	17
16.Packing.....	18



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	4 of 19

1. General Description

E0583A52 is an Active Matrix Electrophoretic Display (AMEPD), with interface and a reference system design. The 5.83" active area contains 648×480 pixels, and has B/W/R/Y full display capabilities. An integrated circuit contains gate buffer, source buffer, interface, timing control logic, oscillator, DC-DC, SRAM, LUT, VCOM and border are supplied with each panel.

2. Features

- 648×480 pixels display
- High contrast
- High reflectance
- Ultra wide viewing angle
- Ultra low power consumption
- Pure reflective mode
- Bi-stable display
- Commercial temperature range
- Landscape, portrait modes
- Hard-coat antiglare display surface
- Ultra Low current deep sleep mode
- On chip display RAM
- Low voltage detect for supply voltage
- High voltage ready detect for driving voltage
- Internal temperature sensor
- Waveform stored in On-chip OTP
- Serial peripheral interface available
- On-chip oscillator
- On-chip booster and regulator control for generating VCOM, Gate and Source driving voltage
- I2C signal master interface to read external temperature sensor/ built-in temperature sensor

3. Typical Application

Electronic Shelf Label System


4. Mechanical Specifications

Parameter	Specifications	Unit	Remark
Screen Size	5.83	Inch	
Display Resolution	480(H)×648(V)	Pixel	Dpi:138
Active Area	118.78(H)×88.22(V)	mm	
Pixel Pitch	0.1833×0.1838	mm	
Pixel Configuration	Rectangle		
Outline Dimension	125.4(H)×99.5 (V) ×0.9(D)	mm	
Weight	31±0.2	g	



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	5 of 19

5. Mechanical Drawing of EPD module





File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	6 of 19

6. Input/output Terminals

Pin #	Single	Description	Remark
1	NC	No connection and do not connect with other NC pins	Keep Open
2	GDR	N-Channel MOSFET Gate Drive Control	
3	RESE	Current Sense Input for the Control Loop	
4	NC	No connection and do not connect with other NC pins	Keep Open
5	VSH2	Positive Source driving voltage	
6	TSCL	I ² C Interface to digital temperature sensor Clock pin, Must pull high or low if not used	
7	TSDA	I ² C Interface to digital temperature sensor Clock pin, Must pull high or low if not used	
8	BS1	Bus selection pin	Note 6-5
9	BUSY	Busy state output pin	Note 6-4
10	RES #	Reset signal input.	Note 6-3
11	D/C #	Data /Command control pin	Note 6-2
12	CS #	The chip select input connecting to the MCU.	Note 6-1
13	SCL	Serial clock pin for interface.	
14	SDA	Serial data pin for interface.	
15	VDDIO	Power input pin for the Interface.	
16	VCI	Power Supply pin for the chip	
17	VSS	Ground (Digital)	
18	VDD	Core logic power pin	
19	VPP	Power Supply for OTP Programming	
20	VSH1	Positive Source driving voltage	
21	VGH	Power Supply pin for Positive Gate driving voltage	
22	VSL	Negative Source driving voltage	
23	VGL	Power Supply pin for Negative Gate driving voltage	
24	VCOM	VCOM driving voltage	

Note 6-1: This pin (CS#) is the chip select input connecting to the MCU. The chip is enabled for MCU communication: only when CS# is pulled LOW.

Note 6-2: This pin (D/C#) is Data/Command control pin connecting to the MCU.



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	7 of 19

When the pin is pulled HIGH, the data will be interpreted as data. When the pin is pulled LOW, the data will be interpreted as command.

Note 6-3: This pin (RES#) is reset signal input. The Reset is active low.


Note 6-4: This pin (BUSY) is Busy state output pin. When Busy is Low ,the operation of chip should not be interrupted and any commands should not be issued to the module. The driver IC will put Busy pin Low when the driver IC is working such as:

- Outputting display waveform; or
- Communicating with digital temperature sensor

Note 6-5: This pin (BS1) is for 3-line SPI or 4-line SPI selection. When it is "Low", 4-line SPI is selected. When it is "High", 3-line SPI (9 bits SPI) is selected.

7. Reference Circuit

Figure. 7-1





File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	8 of 19

Figure. 7-2




Table. 7-3

Part Name	Value /quirement/Reference Part
C1-C3	1uF/0603;X5R/X7R;Voltage Rating: 6V or 25V
C4-C6	1uF/0603;X5R/X7R;Voltage Rating: 50V
C7-C9	1uF/0603;X5R/X7R;Voltage Rating: 25V
C10	1uF/0603; X5R/X7R;Voltage Rating: 25V
D1—D3	MBR0530
	1) Reverse DC voltage $\geq 30V$
	2) Forward current $\geq 500mA$
	3)Forward voltage $\leq 430mV$
R2	2.2 Ω /0603; 1% variation
Q1	NMOS:Si1304BDL/NX3008NBK
	1) Drain-Source breakdown voltage $\geq 30V$
	2) Vgs (th) =0.9 (Typ) , 1.3V (Max)
	3) Rds on $\leq 2.1 \Omega$ @ Vgs=2.5V
L1	47uH/CDRH2D18、LDNP-470NC



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	9 of 19

8. ABSOLUTE MAXIMUM RATING

Parameter	Symbol	Rating	Unit	Humidity	Unit	Note
Logic Supply voltage	VCC,VDDIO	-0.3~6.0	V	45~70	%RH	Note 8-1
Operation temperature range	TOPR	0~40	℃	45~70	%RH	
Storage temperature range	TSTG	-25~50	℃	45~70	%RH	Note 8-2
Transportation temperature range	TTTG	-25~50	℃	45~70	%RH	Note 8-3
GND	Ground	-	-		-	Connect to Ground

Note 8-1: Maximum ratings are those values beyond which damages to the device may occur. VCC: Digital power, VDDIO: IO power. Functional operation should be restricted to the limits in the Electrical Characteristics chapter.

Note 8-2: The display effect may be affected if the product is stored for more than 10days under the environment of 40-50 degree.

Note 8-3: TTTG is the transportation condition, the transport time is within 10 days for -25℃~0℃ or 40℃~50℃

Note 8-4: The single pixel effect under the condition of above 35 degree cannot be guaranteed.Normal use is recommended to refresh every 24 hours.

Note 8-5: Due to the nature of FPL, we will not control the display effect of white characters on yellow and yellow characters on white.

9. DC Characteristics

The following specifications apply for: VSS=0V, VCC=3.0V, TOPR=25±2℃.

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
VDD	VDD operation voltage	-	2.4	3.0	3.6	V
VIH	High level input voltage	-	0.7xVIO	-	VIO	V
VIL	Low level input voltage	-	GND	-	0.3xVDD	V
VOH	High level output voltage	IOH = 400μA	VIO-0.4	-	-	V
VOL	Low level output voltage	IOL = -400μA	GND	-	GND+0.4	V
Iupdate	Module operating current	-	-	3	-	mA
Isleep	Deep sleep mode	VCI=3.3V	-	-	3	uA

- The listed electrical/optical characteristics are only guaranteed under the controller & waveform provided by XingTai.

- VCOM value will be OTP before in factory.

10. Power Consumption

Parameter	Symbol	Conditions	TYP	Max	Unit	Remark
Panel power consumption during update	-	25℃	-	360	mAs	-


MAs=update Average current ×update time

The power consumption is measured using associated 25℃ waveform with following



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	10 of 19

pattern transition:



11. Optical characteristics

11.1 Optical Measurement Conditions

Item	Symbol	Value	Unit	Note
Ambient Temperature	Ta	25±2	°C	Indoor testing
Ambient Humidity	Ha	50±5	%RH	-
Supply Voltage	VCC, VDDIO	3.0	V	-
illuminance	-	800~1300	Lux	

Note 11-1: Image is updated with above condition

11.2 Optical Measurement

T=25°C, VDD=3.3V

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT	Note
R	Reflectance	White	30	35	-	%	Note 15-1
Gn	2Grey Level	-	-	$KS+(WS-KS) \times n(m-1)$	-	L*	-
CR	Contrast Ratio	-	-	10	-	-	-
KS	Black State L* value	-	-	9	14	-	Note 15-1
	Black State a* value	-	-	≤7	-	-	Note 15-1
WS	White State L* value	-	63	65	-	-	Note 15-1
	White State b* value	-	-	2.5	-	-	Note 15-1
RS	Red State L* value	Red	25	26	28		Note 15-1
	Red State a* value	Red	38	40	-		Note 15-1
YS	Yellow State L* value	Yellow	55	58	62		Note 15-1
	Yellow State b* value	Yellow	63	68	-		Note 15-1
Panel	Image Update	Storage and transportation	-	Update the white screen	-	-	-
	Update Time	Operation	-	Suggest Updated once	-	-	-



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	11 of 19


				a day			
--	--	--	--	-------	--	--	--

Remarks:

1. Test instrument: i-one (D50 light source 2 ° viewing angle)
2. All optical data are test values in T0 state; (T0 is the status of the first EPD refresh test);
3. Chosting judges based on optical data, not visual standards; Calculate formula ΔE_{2000} ;

11.3 Definition of contrast ratio

The contrast ratio (CR) is the ratio between the reflectance in a full white area (Rl) and the reflectance in a dark area (Rd): Rl: white reflectance Rd: dark reflectance
$$CR = Rl/Rd$$



11.4 Reflection Ratio


The reflection ratio is expressed as:

$R = \text{Reflectance Factor white board} \times (L_{\text{center}} / L_{\text{white board}})$

L_{center} is the luminance measured at center in a white area ($R=G=B=1$). $L_{\text{white board}}$ is the luminance of a standard white board. Both are measured with equivalent illumination source. The viewing angle shall be no more than 2 degrees.



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	12 of 19



12. Handling Safety and Environmental Requirements

WARNING

The display module should be kept flat or fixed to a rigid, curved support with limited bending along the long axis. It should not be used for continual flexing and bending. Handle with care. Should the display break do not touch any material that leaks out. In case of contact with the leaked material then wash with water and soap.

CAUTION

The display module should not be exposed to harmful gases, such as acid and alkali gases, which corrode electronic components.

Disassembling the display module can cause permanent damage and invalidate the warranty agreements.

IPA solvent can only be applied on active area and the back of a glass. For the rest part, it is not allowed.

Observe general precautions that are common to handling delicate electronic components. The glass can break and front surfaces can easily be damaged. Moreover the display is sensitive to static electricity and other rough environmental conditions.

Mounting Precautions

(1) It's recommended that you consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module.

(2) It's recommended that you attach a transparent protective plate to the surface in order to protect the EPD. Transparent protective plate should have sufficient strength in order to resist external force.

(3) You should adopt radiation structure to satisfy the temperature specification.

(4) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the PS at high temperature and the latter causes circuit break by electro-chemical reaction.



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	13 of 19

(5) Do not touch, push or rub the exposed PS with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of PS for bare hand or greasy cloth. (Some cosmetics deteriorate the PS)

(6) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach the PS. Do not use acetone, toluene and alcohol because they cause chemical damage to the PS.

(7) Wipe off saliva or water drops as soon as possible. Their long time contact with PS causes deformations and color fading.

Data sheet status

Product specification

The data sheet contains final product specifications.

Limiting values

Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information

Where application information is given, it is advisory and does not form part of the specification.

Product Environmental certification

ROHS

REMARK

All The specifications listed in this document are guaranteed for module only. Post-assembled operation or component(s) may impact module performance or cause unexpected effect or damage and therefore listed specifications is not warranted after any Post-assembled operation.



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	14 of 19

13. Reliability test

13.1 Reliability test items

	TEST	CONDITION	METHOD	REMARK
1	High-Temperature Operation	T=40°C, RH=35%RH, For 240Hr		
2	Low-Temperature Operation	T = 0°C for 240 hrs		
3	High-Temperature Storage	T=50°C RH=35%RH For 240Hr Test in white pattern		
4	Low-Temperature Storage	T = -25°C for 240 hrs Test in white pattern		
5	High Temperature, High-Humidity Operation	T=40°C, RH=90%RH, For 168Hr		
6	High Temperature, High-Humidity Storage	T=50°C, RH=90%RH, For 240Hr Test in white pattern		
7	Temperature Cycle	-25°C(30min)~60°C(30min), 50 Cycle Test in white pattern		
8	Package Vibration	1.04G, Frequency : 10~500Hz Direction : X,Y,Z Duration:1hours in each direction	Full packed for shipment	
9	Package Drop Impact	Drop from height of 100 cm on Concrete surface Drop sequence:1 corner, 3edges, 6face One drop for each.	Full packed for shipment	
10	UV exposure Resistance	765 W/m ² for 168hrs,40°C		
11	ESD test	Machine model: +/-250V,0Ω,200pF		

Actual EMC level to be measured on customer application.

Note1: Stay white pattern for storage and non-operation test.

Note2: Power off duration time is 30s

Note3: The function, appearance, optical should meet the requirements of the test before and after the test.

Note4: Continue testing after 2 hours at 20C~25C°C



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	15 of 19


13.2 Product life time

The EPD Module is designed for a 5-year life-time with 25 °C/60%RH operation assumption. Reliability estimation testing with accelerated life-time theory would be demonstrated to provide confidence of EPD lifetime.

13.3 Product warranty

Warranty conditions have to be negotiated between Xingtai and individual customers. Xingtai provides 12(one month delivery time) months warranty for all products which are purchased from Xingtai.

14. Block Diagram



15. Shipment inspection specification

15.1 Zone Definition


A Zone: Active Area

B Zone: Border Area



C Zone: From B Zone edge to panel edge



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	16 of 19



15.2 Line/Spot defect size



15.3 Point and line standard

Shipment Inspection Standard						
Equipment: Electrical test fixture, Point gauge						
Outline dimension	125.4(H)×99.5 (V) ×0.9(D)	Unit: mm	Part-A	Active area	Part-B	Border area
Environment	Temperature	Humidity	illuminance	Distance	Time	Angle
	19°C~25°C	55±5%RH	800~1300Lux	300 mm	35Sec	45 °
Defect type	Inspection method	Standard		Part-A	Part-B	
Spot	Electric Display	$D \leq 0.25 \text{ mm}$		Ignore	Ignore	
		$0.25 \text{ mm} < D \leq 0.4 \text{ mm}$		$N \leq 4$	Ignore	
		$0.4 \text{ mm} < D \leq 0.6 \text{ mm}$		$N \leq 1$	Ignore	
		$D > 0.6 \text{ mm}$		Not Allow	Ignore	
Display malfunction	Electric Display	Not Allow		Not Allow	Ignore	
Display error	Electric Display	Not Allow		Not Allow	Ignore	



File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	17 of 19

Scratch or line defect(include dirt)	Visual/Film card	L≤2 mm,W≤0.1 mm	Ignore	Ignore
		2.0mm<L≤9.0mm, 0.1<W≤0.2mm	N≤2	Ignore
		L>9.0 mm,W>0.2 mm	Not Allow	Ignore
PS Bubble	Visual/Film card	D≤0.4mm	Ignore	Ignore
		0.4mm≤D≤0.6mm	N≤4	Ignore
		D>0.6 mm	Not Allow	Ignore
Corner /Edge chipping	Visual/Film card	X≤8mm,Y≤1mm, Do not affect the electrode circuit (Edge chipping)		
		X≤8mm,Y≤8mm, Do not affect the electrode circuit((Corner chipping)		
		Ignore		
				
TFT warping	For 1.54~7.5inch, T≤2mm; For above 7.5inch, T≤3mm 			
Remark	1.Cannot be defect & failure cause by appearance defect;			
	2.Cannot be larger size cause by appearance defect;			
	L=long W=wide D=point size N=Defects NO			

15.4 Barcode



FF

ABBBBBBBBBB

CCCDDDEEEE

What is the QR code after picture being scanned and read? It consist of 30 numbers and letters, here is explanation for it.

QR Code: ABBBBBBBBBBFFCCCDDDEEEEGHIJKLL

- ① A means Factory code, e.g.: H (HINK)
- ② BBBBBBBBBB refers to product model name, which is in consistent with specification part number. E.g.: E0213A189 or E0266A120; when the total code is less than 9, it would be added suffix with **. e.g.: E027A45** or E0154A78*
- ③ FF means production workshop
- ④ CCC means date of production




File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	18 of 19

- ⑤ DDD means production batch
- ⑥ EEEE means FPL lot
- ⑦ G means MP/Sample/Trial/Repair
- ⑧ HIJ:(H——TFT;I——PS;J——EC Glue)
- ⑨ KK means IC type
- ⑩ LL means serial number

16. Packing

Full carton: 12 pcs tray with products and 1 pcs empty tray.

Last carton: less 12pcs tray with products and 1 pcs empty tray. The packager will add the right amount of EPE to box so that the added EPE's height approximately close to the EPE height around the inside of the box.





兴泰盈科

江西兴泰科技股份有限公司
Jiangxi Xingtai Technology Inc.

File Name	Specification For 5.83" EPD	Module Number	HINK-E0583A52
Version	A0	Page Number	19 of 19

6*12=72 PCS EPD