

[illegible]

 产品外形 焊盘

- 1 Current Rating :0.5A AC/DC max.
- 2 DIELECTRIC WITHSTANDING VOLTAGE :500V AC R.M.S. FOR 1 MINUTE.
- 3 Operation Temperature Range: -25°C~+70°C
- 4 INSULATION RESISTANCE : 100MΩ MIN.AT 500V DC
- 5 Contact Resistance:60mΩ max. SWITCH RESISTANCE : 100mΩ MAX
- 6 OPERATING TEMPERATURE : -30°C TO +85°C
- 7 Durability:5000 cycles

APPROVALS			DATE					
DRAWN		LIUCAN	2024.7.11					
CHECKED					TITLE:		SD	
APPROVALS					PART NO.		TF-04A	
TOLERANCES ARE	30~以上	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:		
	10~30	±0.25						
	5~10	±0.20						
	~ 5	±0.15						
			±2'	DRAWING NO.	_____	SHEET 1 OF		

						CHECKED			TITLE:	SD	
						APPROVALS			PART NO.	TF-04A	
	A		NEW						UNIT: mm	SCALE: 1:1	PROJ:
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	30~以上 10~30 5~10 ~ 5 ±0.30 ±0.25 ±0.20 +0.15 ANGLE ±2'	DRAWING NO.		SHEET 1 OF 1