

Preliminary DATA SHEET

GSM0624: 617 to 652MHz High Linearity 24dBm Power Amplifier

Product overview

GSM0624 is a two-stage HBT small cell power amplifier for indoor cellular base stations. It works at 617~652MHz (NR, n71). This PA can deliver 24dBm output power with ACPR below -50dBc and power gain higher than 28 dB

Key Features

- 617MHz – 652MHz
- 28dB Gain
- 12% PAE at 24dBm output power
- Below -50dBc ACPR at 24dBm linear output power
- Input/output internally matched to 50Ohm
- Integrated temperature compensation circuits
- Compact and low-cost 5mm x 5mm LGA package (MSL3, 260°C per JEDEC J-STD-020)
- ESD Level: HBM 1000V; CDM 1000V
- ROHS compatible

Applications

- FDD/TDD 5G NR systems
- NR operating bands n71 in FR1
- Power amplifier for micro-base stations
- Active antenna array and massive MIMO
- Customer Premises Equipment (CPE)
- Automotive Compensator




Figure1.16 pad 5x5 mm Laminate Package




Figure 2. GSM0624 Function Block Diagram

Table 1. Pin-to-Pin Compatible PA Family

Part Num	Frequency (MHz)	3GPP Band
GSM0724	728-821	B20,B28, n20,n28
GSM0824	869-894	Band 5, n5
GSM0924	925-960	Band 8, n8
GSM1824	1805-1880	Band 3, n3
GSM2124	2110-2170	Band 1,n1
GSM2424	2300-2400	Band 40, n40
GSM2624	2496-2690	Band 41, n41
GSM3524	3300-3600	Band 42,48, n78
GSM3724	3600-3800	Band 43, 48, n78
GSM4024	3700-3980	n77, C Band
GSM5024	4600-5000	n79

Ordering Information

Part No.	Description
GSM0624	617-652MHz 24dBm linear PA, 7' Reel with 1500pcs