



CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

Low Pass Filter
50Ω SMA
7th Order




Part Number: CLPFL-0300

Low Pass Range
DC to 300 MHz



Schematic



Features:


- 7th Order Butterworth Response
- 50Ω SMA Connectors

Applications:

- Test Equipment
- Lab Use

Maximum Ratings:

- +36dBm (4 Watts)
- Operating Temperature: -40°C to 85°C
- Storage Temperature: -55°C to 100°C



Crystek's new line of Low Pass Filters are designed in a rugged SMA housing. This filter line has excellent out-of-band rejection. Designed for Test Equipment and General Lab Use.

Rev C

Page 1 of 3




CRYSTEK
CORPORATION


12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
PHONE: 239-561-3311 • 800-237-3061
FAX: 239-561-1025 • WWW.CRYSTEK.COM




300 MHz Insertion Loss



Male Side Return Loss



Female Side Return Loss





FREQ (MHz)	INSERTION LOSS (dB)	Male Return Loss (dB)	Female Return Loss (dB)
0.3	0.10	40.05	39.82
15.3	0.10	33.41	33.46
30.3	0.19	29.25	29.35
45.3	0.21	26.90	26.83
60.3	0.25	25.39	25.35
75.3	0.31	24.38	24.45
90.3	0.30	23.91	23.84
105	0.35	23.45	23.67
120	0.37	23.65	23.81
135	0.40	23.90	24.24
150	0.45	24.72	25.00
165	0.43	25.98	26.27
180	0.47	27.81	28.24
195	0.53	31.02	31.37
210	0.51	36.80	38.11
225	0.61	38.31	41.23
240	0.62	29.06	29.68
255	0.71	23.42	24.02
270	0.82	19.33	20.03
285	0.95	15.87	16.43
300	1.16	12.88	13.34
330	2.12	7.82	8.23
405	8.84	1.76	1.87
450	14.74	0.95	1.04
510	24.32	0.63	0.60
585	33.83	0.44	0.27
705	58.64	0.30	-0.04
810	50.67	0.26	-0.21
900	48.73	0.11	-0.28
1005	47.89	0.14	-0.33
1245	47.56	0.08	-0.28
1500	49.25	0.06	-0.09
1755	50.04	0.18	0.15
1995	51.19	0.22	0.36
2250	52.29	0.34	0.67
2505	54.06	0.45	0.96
2745	56.02	0.59	1.32
3000	57.97	0.68	1.81

Product Control:

Crystek Part Number:	CLPFL-0300	Release Date:	03-Aug-2015
Revision Level:	C	Responsible:	K. Piotrowicz

Rev C

Page 3 of 3



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Crystek:](#)

[CLPFL-0300](#)