


GENERAL TOLERANCE											
	10 MAX	50 MAX	100 MAX	250 MAX	250 OVR	R5 MAX	R10 MAX	R20 MAX	R20 OVR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±0.2	±0.3	±0.5	±2.5	±3°	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4					±3°	0.1
◎	±0.3	±0.5	±0.8	±1.4	±2					±3°	0.15

PART NO. AND CH. CODE	COLOR
7187-5724	NATURAL
7187-5724-30	BLACK
7187-5724-40	LIGHT GRAY
7187-5724-90	BLUE





注記

1. 適用端子品番 : 7116-6040 ETC.

NOTE

1. APPLICABLE TERMINAL PART NO. : 7116-6040 ETC.



										CUSTOMER						MATL. SPEC.				PBT(SEE TABLE)		TREAT. & FIN.			
										CUSTOMER PART NO.				CUSTOMER DWG NO.											
△ 2010/10/15 CHANGED PART NAME C10-ZA56 M. M																				NAME △ HLC 8.0 2P HOUSING FEMALE					
2010/02/01 NEW C10-Z058 T. O										OFFICE				TRIAL PART NO.											
LET DATE REVISION RECORD NO. CHKD										VENDOR															
GENERAL TOLERANCE										VENDOR NO.															
										DWG TYPE		DWG SOURCE		DWG DATE		UNIT		SCL		ANGLE		PART NO.		7187-5724 ETC.	
A ±0.15 ±0.2 ±0.3 ±0.5 ±0.75 ±30' 0.1										R		NEW		2010/02/01		mm		2:1		3		CH. CODE			
B ±0.2 ±0.3 ±0.55 ±0.95 ±1.4 ±30' 0.1										APPROVED		CHECKED		CHECKED		DESIGN		DRAWN		DWG NO.		7187-5724:R		SET DWG NO.	
C ±0.3 ±0.5 ±0.8 ±1.4 ±2 ±30' 0.15										S. MIZUSE		_____		R. DE GUZMAN		T. OSADA		M. MALABANAN							
SPECIFIED										2010/10/15		_____		2010/10/15		2008/01/18		2010/10/15				YAZAKI CORPORATION			
MASS																									