

4

3

2

1

used for:

DIN 41651

B

4

13.9

POS.	B ±0.2	Part-N0.
10	17.30	140X10059X
14	22.40	140X10069X
16	24.90	140X10079X
20	30.00	140X10089X
26	37.60	140X10099X
34	47.80	140X10109X
40	55.40	140X10119X
50	68.10	140X10129X
60	80.80	140X10139X
64	85.85	140X10159X

Directive 2002/95/EC
„RoHS“
Compliant

APPROVAL * FREIGABE * DEBLOCAGE * AUTOR/ZACON * APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL * FREIGABE * DEBLOCAGE * AUTOR/ZACON * APPROVAL	

NOTES:

1. INSULATORS: PBT GV, V0, UL 94, GREY RAL 7035
2. OPERATING TEMPERATURE RANGE: -55°C TO +125°C

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH
DO NOT ALTER CAD DRAWING BY HAND

				tolerance			
				2002	date		name
				drawn	11.12.		Parei
				appd.	11.12.		Kühle
				norm	DIN 41651		
				d-old			
							
rev.	description	date	name				

scale:		2:1	
material:		SEE NOTES	
title: STRAIN RELIEF 10-64pos.			
dwg no:		AutoCAD 2000	DIN-A
14K1A013			4
		sh: 1/1	
part no:		SEE TABLE	

4

3

2

1