





RoHS

SPECIFICATIONS

Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40℃ to +105℃

Contact Material:Brass
Contact Plating:Au1U
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230℃ for 30−60 seconds
(260℃ for 10 seconds)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Dimension antitheses list

ITEM	PB	PC	PW	H	W
001		3.0		8.5	2.5
002					

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

CHECK

APPROVE

SCALE

UNIT

SIZE

SHEET

PROJ.

FIT

mm

A4

1/1

◆

深圳市连盛精密连接器有限公司

PART NO.

1020300651

TITLE:

2.54FH H=8.5 W=2.5 1*17 DIP PC3.0 Y型 AU1U
青铜 PA6T

A0 2014.03.28 NEW DRAWING

REV DATE MODIFICATION DESCRIPTION

CHANGE