

WINNIE-M

~35° medium beam. Holder with 35 mm screw hole distance according to Zhaga standard. Compatible with Bender+Wirth 4xx Typ L5 connector.

SPECIFICATION:

Dimensions	Ø 49.8 mm
Height	19.3 mm
Fastening	screw
ROHS compliant	yes ⓘ



LEDiL

MATERIALS:


Component	Type	Material	Colour	Finish	Length
C14233_WINNIE-M	Single lens	PMMA	clear		49.6
C14235_WINNIE-HOLDER	Holder	PC	white		49.8

ORDERING INFORMATION:

Quantities for one set:

Single lens	1
Holder	1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C14233_WINNIE-M » Box size: 480 x 280 x 300 mm	Single lens	364	84	28	6.5
C14235_WINNIE-HOLDER » Box size: 480 x 280 x 300 mm	Holder	1820	84	28	7.2





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):




LED V18 Gen6
FWHM / FWTM 58.0° / 113.0°
Efficiency 88 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED V6 Gen6
FWHM / FWTM 27.0° / 58.0°
Efficiency 86 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED V8 Gen6
FWHM / FWTM 31.0° / 70.0°
Efficiency 85 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):




LED VERO10
FWHM / FWTM 36.0° / 74.0°
Efficiency 89 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

CITIZEN


LED CLL01x
FWHM / FWTM 27.0° / 60.0°
Efficiency 85 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

CITIZEN



LED CLL02x/CLU02x (LES10)
FWHM / FWTM 35.0° / 72.0°
Efficiency 87 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



OPTICAL RESULTS (MEASURED):

CITIZEN



LED CLL02x/CLU02x (LES10)
 FWHM / FWTM 35.0° / 72.0°
 Efficiency 86 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 Bender Wirth: 434 Typ L5



Light distribution files

CITIZEN



LED CLL03x/CLU03x
 FWHM / FWTM 49.0° / 95.0°
 Efficiency 86 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 Bender Wirth: 433 Typ L5



Light distribution files

CITIZEN

LED CLU700/701/702/703
 FWHM / FWTM 28.0° / 58.0°
 Efficiency 87 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 Bender Wirth: 434 Typ L5





Light distribution files

OPTICAL RESULTS (MEASURED):

CITIZEN



LED CLU700/701/702/703
FWHM / FWTM 27.0° / 56.0°
Efficiency 89 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

CITIZEN



LED CLU710/711
FWHM / FWTM 32.0° / 70.0°
Efficiency 86 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

CITIZEN

LED CLU710/711
FWHM / FWTM 33.0° / 67.0°
Efficiency 87 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 470 Typ L5





Light distribution files

OPTICAL RESULTS (MEASURED):

CITIZEN



LED CLU720/721/723
FWHM / FWTM 41.0° / 80.0°
Efficiency 90 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 433 Typ L5



Light distribution files




LED CXA/B 13xx
FWHM / FWTM 25.0° / 55.0°
Efficiency 88 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED CXA/B 13xx
FWHM / FWTM 26.0° / 58.0°
Efficiency 87 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



OPTICAL RESULTS (MEASURED):





LED CXA/B 25xx
FWHM / FWTM 55.0° / 109.0°
Efficiency 85 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED MHD-E/G
FWHM / FWTM 30.0° / 67.0°
Efficiency 87 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED LUXEON CoB 1202/1203
FWHM / FWTM 34.0° / 74.0°
Efficiency 86 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



OPTICAL RESULTS (MEASURED):




LED LUXEON CoB 1202s
FWHM / FWTM 27.0° / 60.0°
Efficiency 86 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



[Light distribution files](#)




LED CxM-14 (19x19)
FWHM / FWTM 45.0° / 94.0°
Efficiency 85 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



[Light distribution files](#)



LED CxM-9 (13.5x13.5)
FWHM / FWTM 36.0° / 76.0°
Efficiency 87 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



[Light distribution files](#)

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors


LED Duris S10
FWHM / FWTM 24.0° / 58.0°
Efficiency 88 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



[Light distribution files](#)

OSRAM
Opto Semiconductors


LED Soleriq S13
FWHM / FWTM 41.0° / 88.0°
Efficiency 85 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



[Light distribution files](#)

OSRAM
Opto Semiconductors

LED Soleriq S19
FWHM / FWTM 55.0° / 104.0°
Efficiency 83 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:





[Light distribution files](#)

OPTICAL RESULTS (MEASURED):

SAMSUNG



LED LC016D / LC019D / LC026D / LC033D
FWHM / FWTM 48.0° / 98.0°
Efficiency 85 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files





LED MJT COB LES 14.5
FWHM / FWTM 51.0° / 101.0°
Efficiency 84 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 433 Typ L5



Light distribution files



LED MJT COB LES 9.8
FWHM / FWTM 36.0° / 75.0°
Efficiency 89 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 434 Typ L5





Light distribution files

OPTICAL RESULTS (MEASURED):





LED ZC12/18
FWHM / FWTM 46.0° / 91.0°
Efficiency 87 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 433 Typ L5



Light distribution files





LED DMC 124 / 125
FWHM / FWTM 44.0° / 84.0°
Efficiency 88 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 433 Typ L5



Light distribution files



LED DMC 128
FWHM / FWTM 50.0° / 96.0°
Efficiency 87 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 433 Typ L5




Light distribution files

OPTICAL RESULTS (SIMULATED):

CITIZEN


LED	CLL02x/CLU02x (LES10)
FWHM / FWTM	35.0° / 72.0°
Efficiency	92 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files




LED	CXA/B 15xx
FWHM / FWTM	33.0° / 68.0°
Efficiency	93 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files



LED	LUXEON CoB 1202/1203
FWHM / FWTM	34.0° / 69.0°
Efficiency	89 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Bender Wirth: 441 Typ L5

Light distribution files

OPTICAL RESULTS (SIMULATED):



LED	LUXEON CoB Compact
FWHM / FWTM	27.0° / 60.0°
Efficiency	86 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files



LED	CxM-14 (19x19)
FWHM / FWTM	49.0° / 95.0°
Efficiency	86 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Bender Wirth: 433 Typ L5

Light distribution files



LED	CxM-9 (13.5x13.5)
FWHM / FWTM	35.0° / 72.0°
Efficiency	86 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	


Bender Wirth: 434 Typ L5

Light distribution files

OPTICAL RESULTS (SIMULATED):




LED COB S-Type (LES 6)
 FWHM / FWTM 25.0° / 53.0°
 Efficiency 92 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED Soleriq S9
 FWHM / FWTM 32.0° / 71.0°
 Efficiency 90 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LC003D / LC006D / LC009D / LC013D
 FWHM / FWTM 36.0° / 74.0°
 Efficiency 92 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files


OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED LC010C
FWHM / FWTM 27.0° / 56.0°
Efficiency 92 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Bender Wirth: 479 Typ L5

Light distribution files




SAMSUNG

LED LC020C
FWHM / FWTM 32.0° / 66.0°
Efficiency 90 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Bender Wirth: 479 Typ L5

Light distribution files




SAMSUNG

LED LC040C
FWHM / FWTM 40.0° / 82.0°
Efficiency 89 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Bender Wirth: 479 Typ L5

Light distribution files



OPTICAL RESULTS (SIMULATED):

 SEOUL SEMICONDUCTOR	
LED	ZC4/6
FWHM / FWTM	35.0° / 72.0°
Efficiency	86 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
Bender Wirth: 434 Typ L5	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)