


REV	ECN NO.	APPD
A	HG-20-0043	PRUDJM




规格 Specifications

额定负荷 Rating	DC 12V/50mA
接触电阻 Contact Resistance	100mΩ max.
绝缘电阻 Insulation resistance	DC:100V 60S 100MΩ min.
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S min.
操作力 Operation force	160±40gf
寿命试验 Operating Life	100,000 cycles
行程 Travels	0.20±0.1mm




RECOMMENDED P.C.B. LAYOUT

安装尺寸图



CIRCUIT DIAGRAM

回路图



PRODUCT NO. : 1TS008A*****A1 - CT

轻触开关

3X4立式小龟系列

外形:

按钮颜色:

底座颜色:

盖板颜色:

操作力度:

160=180gf

180=180gf

250=250gf

手感:

0=常规

1=大手感

2=小手感

材料:

0=初始材料

1=新增材料

依次增加

编带

非编带, 不启用

产品高度 (H):

200=2.00mm

250=2.50mm

X. ± 0.3	X' ± 3'	UNITS	PART NAME	QUANTITY	MATERIAL	FINISH
X ± 0.2	X' ± 2'	MAT'L	NAME(INTENDED USE)	3X4 SERIES	TACT SWITCH	
.XX ± 0.1	.XX' ± 1'		PART NO.(INTENDED USE)	1TS008A-1600-2000A1-CT		
.XXX ± 0.05	.XXX' ± 0.5'	FINISH	APPD:	ZD 5/9/2020	DWG NO.:	1TS008A-1600-2000A1-CT
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.			CHKD:	MHLI 5/9/2020	SCALE	SHEET
			DR:	Y.Y.Chen 5/9/2020	10/1	1/1