






RoHs



CIRCUIT DIAGRAM

E	按钮	PPA	1	黑色
D	盖板	铁盖板	1	镀铜锡
C	弹片	不锈钢	1	镀银
B	本体	PPA	1	黑色
A	卡件	黄铜	1	镀银
ITEM	DESCRIPTION	MATERIAL	QTY	FINSH/COLOR



PCB.WELDING DRAWING


The Main Thchnology Performance

Rate voltage,current	50mA DC12V
Contact resistance	≤100mΩ
Operating force	±50gf
Travel	0.35±0.10mm
Insulated resistance	≥100MΩ
Dielectric strength	≥250VAC/1min

TS90120-413-AA

按力码 按力可定制
100=10
150=15
280=28

高度码
H4. 3=043
H4. 5=045
H4. 8=048
H5. 0=050
H5. 5=055
...
H18. 0=180

GENERAL TOLERANCES UNLESS SPECIFIED		 深圳市华明通电子有限公司 Shenzhen Huamingtong Electronics Co., Ltd		
X.X ±0.35	X.° ±5°	PART NO.	TITLE: 12x12 DIP TACT SWITCH	
.XX ±0.25	X.X° ±3°	TS90120-413-AA		
.XXX ±0.15	X.XX° ±1°	DESIGN: James	CUSTOMER	SIZE A4 UNITS MM
MANUFACTURE DWG		CHED: Talen		SCALE N:A
		APPD: Sophia		SHEET 1/1