


Flangeless Termination 250 Watts, 50Ω



Description:

The E250N50X4 is high performance Aluminum Nitride (AlN) termination intended as a cost competitive alternative to Beryllium Oxide (BeO). The termination is well suited to all cellular frequency bands such as; AMPS, GSM, DCS, PCS, PHS and UMTS. The high power handling makes the part ideal for terminating circulators and for use in power combiners. The termination is also RoHS compliant!

Features:

- RoHS Compliant
- 250 Watts
- DC – 2.2GHz
- AlN Ceramic
- Non-Nichrome Resistive Element
- Low VSWR
- 100% Tested

General Specifications:


Resistive Element	Thick film
Substrate	AlN Ceramic
Terminal Finish	Matte Tin over Nickel Barrier
Operating Temperature	-50 to +200°C(see de rating chart)

Electrical Specifications:

Resistance Value:	50 Ohms, $\pm 2\%$
Power:	250 Watts
Frequency Range:	DC – 2.2 GHz
Return Loss	>20 dB DC – 2.2 GHz


Specification based on unit properly installed using suggested mounting instructions and a 50 ohm nominal impedance. **Specifications subject to change.**

Outline Drawing:




Tolerance is ± 0.010 ", unless otherwise specified. $\pm \pm$ Designed to meet or exceed applicable portions of MIL-E-5400. **All dimensions in inches.**

Typical Performance:




Power de-rating:



*Actual performance could be limited by the solder properties of the application

Mounting Footprint:



SUGGESTED MOUNTING PROCEDURE

1. MAKE SURE THAT THE DEVICES ARE MOUNTED ON FLAT SURFACES (.001" UNDER THE DEVICE) TO OPTIMIZE THE HEAT TRANSFER.
2. POSITION DEVICE ON MOUNTING SURFACE AND SOLDER IN PLACE USING AN APPROPRIATE SOLDER.
3. SOLDER LEADS IN PLACE USING AN APPROPRIATE SOLDER TYPE WITH A CONTROLLED TEMPERATURE IRON.

Contact us:
rf&s_support@ttm.com