








PCB LAYOUT
RECOMMENDED

General Specification
Current Rating:1.5A DC /Contact, 20mA DC for LED signals
Voltage Rating:125V AC /Contact, 2.0 volts DC for LED signals
Operating Environment
Standard Temperature: -20℃~+70℃
Industrial Temperature: -40℃~+85℃
Humidity: 20~70%
Contact Resistance:≤30mΩ
Insulation Resistance:≥500MΩ
Dielectric Strength:500V AC/(50HZ)/Min
Mating And Unmating Force:3~20N
Durability:750 Cycles Min

Material Specification
Housing :Thermo-plastic, UL94V-0.
Contact :Alloy Copper
Shield :Alloy Copper
Please refer to the customer drawing when customer has specified



4	外壳	H62	1	NI	
3	LED灯	树脂/FE	2	NI/AG	
2	插针	PHOSPHOR BRONZE	8	1U"	
1	插座	LCP	1	BLACK	
序号	名称	材料	数量	镀层/颜色	备注

网络插座外形图

绘图: 魏飞 日期: 2022.8.01
审核: 魏飞 日期:
核准: 魏飞 日期:



温州瑞川电子有限公司
WEN ZHOU RUI CHUAN ELECTRONIC CO., LTD.

一般公差	品名:	RJ45 TP (带灯带弹)			
90~	±0.25	料号:	8102TP-8YG02411LB19 (WR44115)		
10~30	±0.20	型号:	RJ45	图号:	
~10	±0.16	版本:	单位:mm	比例: 1:1	纸张: A4
角度:	±2°	版本:	单位:mm	比例: 1:1	纸张: A4
页面:	1 of 1	版本:	单位:mm	比例: 1:1	纸张: A4

A/0

新出版发行

变更履历

变更单号

绘制

日期

核准

日期

1

2

3

该图面供温州瑞川电子有限公司内部使用, 不得私自复印