

WQC品牌CBB21电容选型表

容量 (pF)	脚距 (mm)	电压 (V)	尺寸W:H:T (mm)	料号
CBB21 0.22UF	P=7.5MM	450V	9.5*12*7	C352S224J07L230A60
CBB21 0.22UF	P=7.5MM	400V	9.5*12*7	C352G224J07L230A60
CBB21 0.22UF	P=7.5MM	250V	9.5*10.5*5.3	C352E224J07L230A60
CBB21 0.15UF	P=7.5MM	450V	9.5*10.5*5.7	C352S154J07L230A60
CBB21 0.15UF	P=7.5MM	400V	9.5*10.5*5.7	C352G154J07L230A60
CBB21 0.15UF	P=7.5MM	250V	9.5*9.*4.6	C352E154J07L230A60
CBB21 0.1UF	P=7.5MM	450V	9.5*9.5*4.8	C352S104J07L230A60
CBB21 0.1UF	P=7.5MM	400V	9.5*9.5*4.8	C352G104J07L230A60
CBB21 0.1UF	P=7.5MM	250V	9.5*9.5*4.5	C352E104J07L230A60
CBB21 0.082UF	P=7.5MM	450V	9.5*9.8*5.7	C352S823J07L230A60
CBB21 0.082UF	P=7.5MM	400V	9.5*9.8*5.7	C352G823J07L230A60
CBB21 0.082UF	P=7.5MM	250V	9.5*8.5*4.6	C352E823J07L230A60
CBB21 0.068UF	P=7.5MM	450V	9.5*9.5*5.2	C352S683J07L230A60
CBB21 0.068UF	P=7.5MM	400V	9.5*9.5*5.2	C352G683J07L230A60
CBB21 0.068UF	P=7.5MM	250V	9.5*8*4.5	C352E683J07L230A60
CBB21 0.056UF	P=7.5MM	450V	9.5*9*5.1	C352S563J07L230A60
CBB21 0.056UF	P=7.5MM	400V	9.5*9*5.1	C352G563J07L230A60
CBB21 0.056UF	P=7.5MM	250V	9.5*8*4.3	C352E563J07L230A60
CBB21 0.047UF	P=7.5MM	450V	9.5*9*5	C352S473J07L230A60
CBB21 0.047UF	P=7.5MM	400V	9.5*9*5	C352G473J07L230A60
CBB21 0.047UF	P=7.5MM	250V	9.5*8.3*4.3	C352E473J07L230A60
CBB21 0.033UF	P=7.5MM	450V	9.5*8.5*4.6	C352S333J07L230A60

CBB21 0.033UF	P=7. 5MM	400V	9. 5*8. 5*4. 6	C352G333J07L230A60
CBB21 0.033UF	P=7. 5MM	250V	9. 5*8. 5*4. 6	C352E333J07L230A60
CBB21 0.022UF	P=7. 5MM	450V	9. 5*8*4. 5	C352S223J07L230A60
CBB21 0.022UF	P=7. 5MM	400V	9. 5*8*4. 5	C352G223J07L230A60
CBB21 0.022UF	P=7. 5MM	250V	9. 5*8*4. 5	C352E223J07L230A60
CBB21 0.01UF	P=7. 5MM	450V	9. 5*8*4. 2	C352S103J07L230A60
CBB21 0.01UF	P=7. 5MM	400V	9. 5*8*4. 2	C352G103J07L230A60
CBB21 0.01UF	P=7. 5MM	250V	9. 5*8*4. 2	C352E103J07L230A60